

| Comparison                                | PREMIUM RACK SERIES      |                          |                          |                          |
|---|--------------------------|--------------------------|--------------------------|--------------------------|
|   | RSF                      | RSF BYTEline             | RDF                      | RSB                      |
|   | Welded-frame             | Welded-frame             | Welded-frame             | Welded-frame             |
|   | 1.5 and 2 mm sheet steel | 1.5 and 2 mm sheet steel | 1.5 and 2 mm sheet steel | 1.5 and 2 mm sheet steel |
| <b>Appropriate use</b>                    |                          |                          |                          |                          |
| Server rack                               | +++                      | +++                      | ++                       | +++                      |
| Data rack                                 | +++                      | +++                      | +++                      | +                        |
| Cable rack                                | ++                       | ++                       | +++                      | +                        |
| Data centers                              | +++                      | +++                      | +++                      | +++                      |
| <b>Balanced load rating</b>               |                          |                          |                          |                          |
| Up to 800 kg                              | yes                      | yes                      | yes                      | yes                      |
| Up to 1000 kg                             | yes                      | yes                      | -                        | yes                      |
| Up to 1500 kg                             | yes                      | yes                      | -                        | yes                      |
| Up to 1500 kg on 19" extrusions           | yes                      | yes                      | -                        | -                        |
| <b>IP rating</b>                          |                          |                          |                          |                          |
| IP20                                      | yes                      | yes                      | yes                      | yes                      |
| IP40                                      | yes                      | -                        | yes                      | -                        |
| IP54                                      | yes                      | -                        | yes                      | -                        |
| <b>Baying</b>                             |                          |                          |                          |                          |
| Side                                      | yes                      | yes                      | yes                      | yes                      |
| With special sections                     | yes                      | yes                      | yes                      | yes                      |
| <b>Targeted cooling</b>                   |                          |                          |                          |                          |
| Door perforation 86%                      | yes                      | yes                      | yes                      | yes                      |
| Ventilation units                         | yes                      | -                        | yes                      | -                        |
| CoolTop units                             | yes                      | yes                      | yes                      | yes                      |
| Side-mount CoolTeg units                  | yes                      | yes                      | yes                      | yes                      |
| <b>Cabling</b>                            |                          |                          |                          |                          |
| Changeable internal configuration         | yes                      | yes                      | yes                      | yes                      |
| Supports HDWM (Cat. 6A and higher)        | yes                      | yes                      | yes                      | yes                      |
| Supports OptiWay                          | yes                      | yes                      | yes                      | yes                      |
| Supports TopDucts                         | yes                      | yes                      | yes                      | yes                      |
| <b>Size</b>                               |                          |                          |                          |                          |
| 27U                                       | yes                      | -                        | yes                      | -                        |
| 42U                                       | yes                      | yes                      | yes                      | yes                      |
| 45U                                       | yes                      | -                        | yes                      | yes                      |
| 48U                                       | yes                      | -                        | yes                      | yes                      |
| 52U                                       | yes                      | -                        | -                        | -                        |
| <b>Colors</b>                             |                          |                          |                          |                          |
| Black RAL 9005                            | yes                      | yes                      | yes                      | yes                      |
| Light gray RAL 7035                       | yes                      | yes                      | yes                      | yes                      |
| <b>Locking system</b>                     |                          |                          |                          |                          |
| Singlepoint                               | yes                      | -                        | yes                      | yes                      |
| Multipoint                                | yes                      | yes                      | yes                      | -                        |
| <b>Security options</b>                   |                          |                          |                          |                          |
| Access control system                     | yes                      | yes                      | yes                      | yes                      |
| Airflow management                        | yes                      | yes                      | yes                      | yes                      |
| Monitoring indoor and outdoor environment | yes                      | yes                      | yes                      | yes                      |

| Comparison                                | iSEVEN RACK SERIES       |                          |                          |                          |
|---|--------------------------|--------------------------|--------------------------|--------------------------|
|   | R17                      | R17 SERVER               | Flex RM7                 | Flex SERVER              |
|   | Welded-frame             | Welded-frame             | Demountable frame        | Demountable frame        |
|   | Assembled                | Assembled                | Unassembled              | Unassembled              |
|   | 1.5 and 2 mm sheet steel | 1.5 and 2 mm sheet steel | 1.5 and 2 mm sheet steel | 1.5 and 2 mm sheet steel |
|   |                          |                          |                          |                          |
| <b>Appropriate use</b>                    |                          |                          |                          |                          |
| Server rack                               | ++                       | +++                      | +                        | +++                      |
| Data rack                                 | +++                      | +++                      | +++                      | +++                      |
| Cable rack                                | +++                      | ++                       | +++                      | ++                       |
| Data centers                              | +                        | ++                       | +                        | ++                       |
| <b>Balanced load rating</b>               |                          |                          |                          |                          |
| Up to 300 kg                              | yes                      | -                        | yes                      | -                        |
| Up to 500 kg                              | yes                      | -                        | yes                      | -                        |
| Up to 1000 kg                             | -                        | yes                      | -                        | yes                      |
| <b>IP rating</b>                          |                          |                          |                          |                          |
| IP20                                      | yes                      | yes                      | yes                      | yes                      |
| IP30                                      | yes                      | yes                      | yes                      | yes                      |
| <b>Baying</b>                             |                          |                          |                          |                          |
| Side                                      | yes                      | yes                      | yes                      | yes                      |
| <b>Targeted cooling</b>                   |                          |                          |                          |                          |
| Door perforation 86%                      | yes                      | yes                      | yes                      | yes                      |
| Ventilation units                         | yes                      | yes                      | yes                      | yes                      |
| Side mount CoolTeg                        | yes                      | yes                      | yes                      | yes                      |
| <b>Cabling</b>                            |                          |                          |                          |                          |
| Changeable internal configuration         | yes                      | yes                      | yes                      | yes                      |
| Supports HDWM (Cat. 6A and higher)        | yes                      | yes                      | yes                      | yes                      |
| Supports OptiWay                          | yes                      | yes                      | yes                      | yes                      |
| Supports TopDucts                         | yes                      | yes                      | yes                      | yes                      |
| <b>Size</b>                               |                          |                          |                          |                          |
| 15U                                       | yes                      | -                        | yes                      | -                        |
| 21U                                       | yes                      | -                        | yes                      | -                        |
| 27U                                       | yes                      | -                        | yes                      | -                        |
| 33U                                       | yes                      | -                        | yes                      | -                        |
| 42U                                       | yes                      | yes                      | yes                      | yes                      |
| 45U                                       | yes                      | yes                      | yes                      | yes                      |
| 48U                                       | yes                      | -                        | yes                      | -                        |
| <b>Colors</b>                             |                          |                          |                          |                          |
| Black RAL 9005                            | yes                      | yes                      | yes                      | yes                      |
| Light gray RAL 7035                       | yes                      | yes                      | yes                      | yes                      |
| <b>Locking system</b>                     |                          |                          |                          |                          |
| Singlepoint                               | yes                      | yes                      | yes                      | yes                      |
| <b>Security options</b>                   |                          |                          |                          |                          |
| Access control system                     | yes                      | yes                      | yes                      | yes                      |
| Airflow management                        | yes                      | yes                      | yes                      | yes                      |
| Monitoring indoor and outdoor environment | yes                      | yes                      | yes                      | yes                      |